# Safety data sheet for chemical products

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K Black [POSCA]

**JAPAN** 

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

**AUSTRALIA** 

Australian importer : Mitsubishi Pencil Australia

BAN : 31 085 515 671

Address : 674 Lorimar Street, Port Melbourne VIC 3207

Telephone Number : 03 9646 5630

Emergency Telephone Number: 03 9646 5630

(Monday to Friday 9:00am - 5.00pm, general information only)

Creation Date : August 24, 2001 Revision Date : March 7, 2014

File No. : 010275A\_Aus Rev. 3.6.06.05

## 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

No hazardous product as specified in Directive 67/548/EEC or 1999/45/EC

Label elements :-

Other hazards : Not available.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a mixture : Mixture

Chemical nature: Component parts : Ink

| Chemical or generic name | CAS No.    | TSCA       | EINECS No. | Concentration range (wt%) |
|--------------------------|------------|------------|------------|---------------------------|
| Water                    | 7732-18-5  | Registered | 2317912    | 50- 80                    |
| Carbon Black             | 1333-86-4  | Registered | 2156099    | < 10                      |
| Resin                    | Registered | Registered | Registered | < 10                      |
| Ethylene glycol          | 107-21-1   | Registered | 2034733    | < 10                      |
| Ethyl alcohol            | 64-17-5    | Registered | 2005786    | < 10                      |
| 2-Propanol               | 67-63-0    | Registered | 2006617    | < 10                      |

Other parts : Other parts are excluded from 'chemical substances'.

### 4. FIRST-AID MEASURES

#### Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

#### Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

#### Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention. Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 3.6g]

### 5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.

> Use extinguishing agents appropriate for surrounding fire. Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions: Do not wash away into shower or water way. Methods for cleaning up : Wipe off by dry cloth and wash with water.

: In accordance with national, state and local regulations.

## 7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards. Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.

: Recap after use.

: Keep out of the reach of infants. Avoid contact with skin and eyes.

Precautions : Not available. Safe handling advice : Not available.

Storage:

Technical measures : Keep away from oxidizing materials, ignition sources and

high temperature.

: Avoid direct sunlight. Storage condition

: Do not leave the products in high temperature space.

Recommended temperature: 0-30 C.

Incompatible products : Not available. Packaging materials : Not applicable.

Revision Date: March 7, 2014

## 8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

| OSHA  | 3.5mg/m3 TWA                            | Carbon Black    |
|-------|---|-----------------|
|       | 1000ppm TWA                             | Ethyl alcohol   |
|       | 400 ppm TWA, 500ppm STEL                | 2-Propanol      |
| ACGIH | 3.5mg/m3 TWA                            | Carbon Black    |
|       | 100mg/m3 ceiling (particulate)(aerosol) | Ethylene glycol |
|       | 1000ppm TWA                             | Ethyl alcohol   |
|       | 200ppm TWA, 400ppm STEL                 | 2-Propanol      |
| EC    | 3.5mg/m3 TWA                            | Carbon Black    |
|       | 52mg/m3(20ppm) TWA(skin),               | Ethylene glycol |
|       | 104mg/m3(40ppm) STEL(skin)              |                 |
|       | 1000ppm                                 | Ethyl alcohol   |

Personal protective equipment : Not required.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

[ ]: Information of components.

Physical state and form : Liquid.
Color : Black.
Odor : Faint odor.
pH : about 8.5

Boiling point : Not available. [Water/ 100 C]

Melting point :<-10 C

Flash point : Not applicable. [2-Propanol/ 11.7 C] Auto ignition temperature : Not applicable. [Ethyl alcohol/ 363 C]

Explosion limits : Not applicable.

[Lower flammable limit / 2.0%, Upper flammable limit / 12.7% <2-Propanol>]

Density : about 1.1 / 25 C

Vapor density (air=1) : Not available. [2-Propanol/ 2.07-2.10]

Solubility in water : Soluble. Evaporation rate : Not available. Volatile : 78-81%

### 10. STABILITY AND REACTIVITY

Stability : Stability. Hazardous reactions : Will not occur.

Conditions to avoid : Avoid heat, flames, sparks and other sources of ignition.

Avoid contact with incompatible materials.

Materials to avoid : Not available. Hazardous decomposition products : Not available.

## 11.TOXICOLOGICAL INFORMATION

(Information of components)

Acute toxicity

| •               |                                |                                 |
|-----------------|--------------------------------|---------------------------------|
| Ingestion LD50  | >10000mg/kg-Rat                | Carbon Black                    |
|                 | 1650mg/kg-Cat、                 | Ethylene glycol                 |
|                 | 4700mg/kg-Rat                  |                                 |
|                 | 3450mg/kg-Mouse                | Ethyl alcohol                   |
|                 | 3600mg/kg-Mouse                | 2-Propanol                      |
| Inhalation LC50 | 20000ppm-10H-Rat               | Ethyl alcohol                   |
|                 | 11100ppm-4H-Mouse              | 2-Propanol                      |
| Skin LD50       | >3000mg/kg-Rabbit              | Carbon Black                    |
|                 | 9530uL/kg-Rabbit               | Ethylene glycol                 |
|                 | 12800mg/kg-Rabbit              | 2-Propanol                      |
| Local effects   | Irritant;inhalation, skin      | Carbon Black                    |
|                 | Irritant;inhalation, skin, eye | Ethylene glycol / Ethyl alcohol |
|                 | Irritant;inhalation, eye       | 2-Propanol                      |

Chronic toxicity and long term toxicity

Lungs may be affected by repeated or prolonged exposure at very high concentrations. Respiratory disorders.

The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus).

The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration.

Carbon Black

Ethylene glycol

Ethyl alcohol

The liquid defats the skin.

2-Propanol

Signs and Symptoms of overexposure and aggravated by exposure

| Inhalation      | irritation             | Carbon Black / Resin            |
|-----------------|------------------------|---------------------------------|
|                 | irritation,cough       | Ethylene glycol / Ethyl alcohol |
|                 | irritation,nausea      | 2-Propanol                      |
| Skin contact    | irritation             | Carbon Black / Resin            |
|                 | irritation,dry         | Ethylene glycol / Ethyl alcohol |
|                 | irritation, absorption | 2-Propanol                      |
| Eye contact     | mechanical irritation, | Carbon Black                    |
| -               | discoloration of lids  |                                 |
|                 | irritation             | Resin                           |
|                 | irritation,redness     | Ethylene glycol / Ethyl alcohol |
|                 | irritation,pain        | 2-Propanol                      |
| Ingestion       | nausea,vomiting        | Ethylene glycol                 |
|                 | rash, vomiting         | Ethyl alcohol                   |
|                 | nausea,stomach pain    | 2-Propanol                      |
| pecific effects | IARC Group 2B          | Carbon Black                    |
|                 | IARC Group 3           | 2-Propanol                      |
|                 |                        |                                 |

## 12. ECOLOGICAL INFORMATION

Not available.

Revision Date: March

## 13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging: Not applicable.

## 14. TRANSPORT INFORMATION

HS Code : 960820

## 15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS)

: Carbon Black / Ethylene glycol / Ethyl alcohol / 2-Propanol

EU labeling : Not restricted.

CANADA Hazardous Products Act - Ingredient Disclosure List

Carbon Black / Ethylene glycol / 2-Propanol 1%over

0.1%over Ethyl alcohol

Hazard and safety information

Products are manufactured in accordance with ISO 8124-3 " Safety of Toys - Part 3"

### 16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it. The information contained in this sheet are based knowledge of the products at the data: (March 7, 2014). They are given quite sincerely. Moreover the attention of the users is drawn on the risks possibly taken, when a product is used for other utilization than these which it is intended.

# Safety data sheet for chemical products

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K Red [POSCA]

**JAPAN** 

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

AUSTRALIA

Australian importer : Mitsubishi Pencil Australia

BAN : 31 085 515 671

Address : 674 Lorimar Street, Port Melbourne VIC 3207

Telephone Number : 03 9646 5630

Emergency Telephone Number: 03 9646 5630

(Monday to Friday 9:00am - 5.00pm, general information only)

Creation Date : August 24, 2001 Revision Date : March 7, 2014

File No. : 010276A\_Aus Rev. 3.6.08.05

## 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

No hazardous product as specified in Directive 67/548/EEC or 1999/45/EC

Label elements :-

Other hazards : Not available.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a mixture : Mixture

Chemical nature: Component parts : Ink

| Chemical or generic name | CAS No.    | TSCA       | EINECS No. | Concentration range (wt%) |
|--------------------------|------------|------------|------------|---------------------------|
| Water                    | 7732-18-5  | Registered | 2317912    | 50- 80                    |
| Titanium dioxide         | 13463-67-7 | Registered | 2366755    | 10- 30                    |
| Coloring agent           | Registered | Registered | Registered | < 10                      |
| Resins                   | Registered | Registered | Registered | < 10                      |
| Ethylene glycol          | 107-21-1   | Registered | 2034733    | < 10                      |
| Ethyl alcohol            | 64-17-5    | Registered | 2005786    | < 10                      |

Other parts : Other parts are excluded from 'chemical substances'.

### 4. FIRST-AID MEASURES

#### Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

2/5 Creation Date: August 24, 2001 Revision Date: March 7, 2014

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention. Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 3.7g]

### 5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.

Use extinguishing agents appropriate for surrounding fire. Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions: Do not wash away into shower or water way. Methods for cleaning up: Wipe off by dry cloth and wash with water.

: In accordance with national, state and local regulations.

#### 7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards. Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.

: Recap after use.

Keep out of the reach of infants.Avoid contact with skin and eyes.

Precautions : Not available. Safe handling advice : Not available.

Storage:

Technical measures : Keep away from oxidizing materials, ignition sources and

high temperature.

Storage condition : Avoid direct sunlight.

: Do not leave the products in high temperature space.

Recommended temperature: 0-30 C.

Incompatible products : Not available.
Packaging materials : Not applicable.

Revision Date: March 7, 2014

## 8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

| OSHA  | 15mg/m3 TWA (Total dust)                | Titanium dioxide |
|-------|---|------------------|
|       | 1000ppm TWA                             | Ethyl alcohol    |
| ACGIH | 10mg/m3 TWA                             | Titanium dioxide |
|       | 100mg/m3 ceiling (particulate)(aerosol) | Ethylene glycol  |
|       | 1000ppm TWA                             | Ethyl alcohol    |
| EC    | 6mg/m3                                  | Titanium dioxide |
|       | 52mg/m3(20ppm) TWA(skin),               | Ethylene glycol  |
|       | 104mg/m3(40ppm) STEL(skin)              |                  |
|       | 1000ppm                                 | Ethyl alcohol    |

Personal protective equipment : Not required.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

[ ]: Information of components.

Physical state and form : Liquid.
Color : Red.
Odor : Faint odor.
pH : about 8.2

Boiling point : Not available. [Water/ 100 C]

Melting point :<-10 C

Flash point : Not applicable. [Ethyl alcohol/ 12.2 C(CC)] Auto ignition temperature : Not applicable. [Ethyl alcohol/ 363 C]

Explosion limits : Not applicable.

[Lower flammable limit / 3.28%, Upper flammable limit / 19.0% < Ethyl alcohol>]

Density : about 1.1 / 25 C

Vapor density (air=1) : Not available. [Ethyl alcohol/ 1.59]

Solubility in water : Soluble. Evaporation rate : Not available. Volatile : 72-75%

## 10. STABILITY AND REACTIVITY

Stability : Stability. Hazardous reactions : Will not occur.

Conditions to avoid : Avoid heat, flames, sparks and other sources of ignition.

Avoid contact with incompatible materials.

Materials to avoid : Not available. Hazardous decomposition products : Not available.

## 11.TOXICOLOGICAL INFORMATION

#### (Information of components)

Acute toxicity

| Ingestion LD50  | >24000mg/kg-Rat  | Titanium dioxide |
|-----------------|------------------|------------------|
|                 | 1650mg/kg-Cat、   | Ethylene glycol  |
|                 | 4700mg/kg-Rat    |                  |
|                 | 3450mg/kg-Mouse  | Ethyl alcohol    |
| Inhalation LC50 | 6820mg/m3-4H-Rat | Titanium dioxide |
|                 | 20000ppm-10H-Rat | Ethyl alcohol    |
| Skin LD50       | 9530uL/kg-Rabbit | Ethylene glycol  |

Local effects Irritant;inhalation, skin, eye Ethylene glycol / Ethyl alcohol

Chronic toxicity and long term toxicity

The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus).

The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration.

Ethylene glycol

Ethyl alcohol

#### Signs and Symptoms of overexposure and aggravated by exposure

|              | _   |  |
|--------------|---|--|
| Inhalation   | irritation,cough  | Titanium dioxide / Ethylene glycol                     |
|              |   | Ethyl alcohol  |
|              | ,   |  |
|              | irritation  | Coloring agent   |
|              | headache,nausea   | Resin  |
| Skin contact | redness,swelling of skin  | Coloring agent   |
|              | irritation  | Resin  |
|              | irritation,dry  | Ethylene glycol / Ethyl alcohol                        |
| Eye contact  | irritation,redness  | Titanium dioxide / Ethylene glycol                     |
|              | ,   | Ethyl alcohol  |
|              |   |  |
|              | irritation  | Resin  |
| Ingestion    | irritation physiologically inert,intestinal   | Resin<br>Titanium dioxide                              |
| Ingestion    |   |  |
| Ingestion    | physiologically inert,intestinal  |  |
| Ingestion    | physiologically inert,intestinal obstruction  | Titanium dioxide                                       |
| Ingestion    | physiologically inert,intestinal<br>obstruction<br>nausea,vomiting<br>digestive discomfort        | Titanium dioxide  Coloring agent Resin                 |
| Ingestion    | physiologically inert,intestinal obstruction nausea,vomiting digestive discomfort nausea,vomiting | Titanium dioxide  Coloring agent Resin Ethylene glycol |
| Ingestion    | physiologically inert,intestinal<br>obstruction<br>nausea,vomiting<br>digestive discomfort        | Titanium dioxide  Coloring agent Resin                 |

## 12. ECOLOGICAL INFORMATION

Not available.

## 13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging: Not applicable.

## 14. TRANSPORT INFORMATION

HS Code : 960820

# 15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS) : Titanium dioxide / Ethylene glycol / Ethyl alcohol

EU labeling : Not restricted.

CANADA Hazardous Products Act - Ingredient Disclosure List

1%over Ethylene glycol 0.1%over Ethyl alcohol

Hazard and safety information

Products are manufactured in accordance with ISO 8124-3 "Safety of Toys - Part 3"

## 16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it. The information contained in this sheet are based knowledge of the products at the data: (March 7, 2014). They are given quite sincerely. Moreover the attention of the users is drawn on the risks possibly taken, when a product is used for other utilization than these which it is intended.

# Safety data sheet for chemical products

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K Blue [POSCA]

**JAPAN** 

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

**AUSTRALIA** 

Australian importer : Mitsubishi Pencil Australia

BAN : 31 085 515 671

Address : 674 Lorimar Street, Port Melbourne VIC 3207

Telephone Number : 03 9646 5630

Emergency Telephone Number: 03 9646 5630

(Monday to Friday 9:00am - 5.00pm, general information only)

Creation Date : August 24, 2001 Revision Date : March 7, 2014

File No. : 010277A\_Aus Rev. 3.6.06.05

### 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

No hazardous product as specified in Directive 67/548/EEC or 1999/45/EC

Label elements :-

Other hazards : Not available.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a mixture : Mixture

Chemical nature: Component parts : Ink

| Chemical or generic name | CAS No.    | TSCA       | EINECS No. | Concentration range (wt%) |
|--------------------------|------------|------------|------------|---------------------------|
| Water                    | 7732-18-5  | Registered | 2317912    | 50- 80                    |
| Titanium dioxide         | 13463-67-7 | Registered | 2366755    | 10- 30                    |
| Resins                   | Registered | Registered | Registered | < 10                      |
|                          |            |            | Polymer    |                           |
| Ethyl alcohol            | 64-17-5    | Registered | 2005786    | < 10                      |
| 2-Propanol               | 67-63-0    | Registered | 2006617    | < 10                      |
| Coloring agents          | Registered | Registered | Registered | < 10                      |
| Ethylene glycol          | 107-21-1   | Registered | 2034733    | < 10                      |
| Silica (amorphous)       | 7631-86-9  | Registered | 2315454    | < 10                      |
| Additive                 | Registered | Registered | Registered | < 10                      |

Other parts : Other parts are excluded from 'chemical substances'.

Revision Date: March 7, 2014

### 4. FIRST-AID MEASURES

#### Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

#### Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

#### Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

#### Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 4.1g]

## 5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.

Use extinguishing agents appropriate for surrounding fire. Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions: Do not wash away into shower or water way. Methods for cleaning up: Wipe off by dry cloth and wash with water.

: In accordance with national, state and local regulations.

## 7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards.

Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.

: Recap after use.

Keep out of the reach of infants.Avoid contact with skin and eyes.

Precautions : Not available. Safe handling advice : Not available.

Storage:

Technical measures : Keep away from oxidizing materials, ignition sources and

high temperature.

Storage condition : Avoid direct sunlight.

: Do not leave the products in high temperature space.

: Recommended temperature: 0-30 C.

Incompatible products : Not available. Packaging materials : Not applicable.

## 8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

| OSHA  | 15mg/m3 TWA (Total dust) 1000ppm TWA 400 ppm TWA, 500ppm STEL 5mg/m3(Respirable fraction), 15mg/m3(Total dust) [Nuisance Dust] 5mg/m3(as Mo), 1mg/m3(as W) | Titanium dioxide<br>Ethyl alcohol<br>2-Propanol<br>Coloring agent |
|-------|--|---|
|       | [Soluble compounds] 20mppcf TWA (<1% crystalline silica)   | Silica (amorphous)  |
| ACGIH | 10mg/m3 TWA  | Titanium dioxide<br>Coloring agent                                |
|       | 1000ppm TWA  | Ethyl alcohol   |
|       | 200ppm TWA, 400ppm STEL  | 2-Propanol  |
|       | 5mg/m3(as Mo), 1mg/m3(as W)<br>[Soluble compounds]   |   |
|       | 100mg/m3 ceiling (particulate)(aerosol)  | Ethylene glycol   |
| EC    | 6mg/m3   | Titanium dioxide  |
|       | 1000ppm  | Ethyl alcohol   |
|       | 52mg/m3(20ppm) TWA(skin),<br>104mg/m3(40ppm) STEL(skin)  | Ethylene glycol   |

Personal protective equipment : Not required.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

[ ]: Information of components.

Physical state and form : Liquid.
Color : Not available.

Odor : Blue. pH : about 8.4

Boiling point : Not available. [Water/ 100 C]

Melting point : <-10 C

Flash point : Not applicable. [2-Propanol/ 11.7 C]
Auto ignition temperature : Not applicable. [Ethyl alcohol/ 363 C]

Explosion limits : Not applicable.

[Lower flammable limit / 2.0%, Upper flammable limit / 12.7% <2-Propanol>]

Density : about 1.2 / 25 C

Vapor density (air=1) : Not available. [2-Propanol/ 2.07-2.10]

Solubility in water : Soluble. Evaporation rate : Not available. Volatile : 63-66%

## 10. STABILITY AND REACTIVITY

Stability Stability. Hazardous reactions Will not occur.

Conditions to avoid Avoid heat, flames, sparks and other sources of ignition.

Avoid contact with incompatible materials.

Materials to avoid : Not available. Hazardous decomposition products : Not available.

## 11.TOXICOLOGICAL INFORMATION

## (Information of components)

Acute toxicity

| Ingestion LD50  | >24000mg/kg-Rat      | Titanium dioxide   |
|-----------------|----------------------|--------------------|
|                 | 3450mg/kg-Mouse      | Ethyl alcohol      |
|                 | 3600mg/kg-Mouse      | 2-Propanol         |
|                 | $\geq$ 5000mg/kg-Rat | Coloring agent     |
|                 | 1650mg/kg-Cat        | Ethylene glycol    |
|                 | 4700mg/kg-Rat        |                    |
|                 | 3160mg/kg-Rat        | Silica (amorphous) |
| Inhalation LC50 | 6820mg/m3-4H-Rat     | Titanium dioxide   |
|                 | 20000ppm-10H-Rat     | Ethyl alcohol      |
|                 | 11100ppm-4H-Mouse    | 2-Propanol         |
| Skin LD50       | 12800mg/kg-Rabbit    | 2-Propanol         |
|                 | 9530uL/kg-Rabbit     | Ethylene glycol    |
|                 |                      |                    |

Local effects Irritant; inhalation, skin, eye Ethyl alcohol / Ethylene glycol

> Irritant; inhalation, eye 2-Propanol

Chronic toxicity and long term toxicity

The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of

concentration. .

The liquid defats the skin. The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus). Ethyl alcohol

2-Propanol Ethylene glycol

#### Signs and Symptoms of overexposure and aggravated by exposure

| Inhalation   | irritation,cough       | Titanium dioxide / Ethyl alcohol<br>Ethylene glycol / Silica (amorphous) |
|--------------|------------------------|--|
|              | irritation             | Resin / Coloring agent   |
|              | irritation,nausea      | 2-Propanol   |
| Skin contact | irritation             | Resin  |
|              | irritation,dry         | Ethyl alcohol / Ethylene glycol  |
|              |                        | Silica (amorphous)   |
|              | irritation, absorption | 2-Propanol   |
| Eye contact  | irritation,redness     | Titanium dioxide / Ethyl alcohol   |
| v            |                        | Ethylene glycol / Silica (amorphous)                                     |
|              | irritation             | Resin / Coloring agent   |
|              | irritation,pain        | 2-Propanol   |

Ingestion physiologically inert, Titanium dioxide

intestinal obstruction

rash,vomiting
nausea,stomach pain
gastric disturbances
nausea,vomiting

Ethyl alcohol
2-Propanol
Coloring agent
Ethylene glycol

Specific effects IARC Group 2B Titanium dioxide

IARC Group 3 2-Propanol / Silica (amorphous)

## 12. ECOLOGICAL INFORMATION

Not available.

### 13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging: Not applicable.

## 14. TRANSPORT INFORMATION

HS Code : 960820

## 15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS)

: Titanium dioxide / Ethyl alcohol / 2-Propanol / Ethylene glycol

EU labeling : Not restricted.

CANADA Hazardous Products Act - Ingredient Disclosure List

0.1%over Ethyl alcohol

1%over 2-Propanol / Ethylene glycol / Silica (amorphous)

Hazard and safety information

Products are manufactured in accordance with ISO 8124-3 " Safety of Toys - Part 3"

## 16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it. The information contained in this sheet are based knowledge of the products at the data: (March 7, 2014). They are given quite sincerely. Moreover the attention of the users is drawn on the risks possibly taken, when a product is used for other utilization than these which it is intended.

# Safety data sheet for chemical products

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K Green [POSCA]

**JAPAN** 

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

**AUSTRALIA** 

Australian importer : Mitsubishi Pencil Australia

BAN : 31 085 515 671

Address : 674 Lorimar Street, Port Melbourne VIC 3207

Telephone Number : 03 9646 5630

Emergency Telephone Number: 03 9646 5630

(Monday to Friday 9:00am - 5.00pm, general information only)

Creation Date : August 24, 2001 Revision Date : March 7, 2014

File No. : 010278A\_Aus Rev. 3.6.07.05

## 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

No hazardous product as specified in Directive 67/548/EEC or 1999/45/EC

Label elements :-

Other hazards : Not available.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a mixture : Mixture

Chemical nature: Component parts: Ink

| Chemical or generic name | CAS No.    | TSCA       | EINECS No. | Concentration range (wt%) |
|--------------------------|------------|------------|------------|---------------------------|
| Water                    | 7732-18-5  | Registered | 2317912    | 50- 80                    |
| Titanium dioxide         | 13463-67-7 | Registered | 2366755    | 10- 30                    |
| Resins                   | Registered | Registered | Registered | < 10                      |
| Coloring agents          | Registered | Registered | Registered | < 10                      |
| Ethylene glycol          | 107-21-1   | Registered | 2034733    | < 10                      |
| Ethyl alcohol            | 64-17-5    | Registered | 2005786    | < 10                      |

Other parts : Other parts are excluded from 'chemical substances'.

### 4. FIRST-AID MEASURES

#### Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

2/5 Creation Date: August 24, 2001 Revision Date: March 7, 2014

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention. Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 3.9g]

### 5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.

Use extinguishing agents appropriate for surrounding fire. Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions: Do not wash away into shower or water way. Methods for cleaning up: Wipe off by dry cloth and wash with water.

: In accordance with national, state and local regulations.

#### 7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards. Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.

: Recap after use.

Keep out of the reach of infants.Avoid contact with skin and eyes.

Precautions : Not available. Safe handling advice : Not available.

Storage:

Technical measures : Keep away from oxidizing materials, ignition sources and

high temperature.

Storage condition : Avoid direct sunlight.

: Do not leave the products in high temperature space.

Recommended temperature: 0-30 C.

Incompatible products : Not available. Packaging materials : Not applicable.

## 8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

| OSHA  | 15mg/m3 TWA (Total dust)                | Titanium dioxide   |
|-------|---|--------------------|
|       | 15mg/m3 PEL (Nuisance Dust)             | Coloring agent     |
|       | 1000ppm TWA                             | Ethyl alcohol      |
| ACGIH | 10mg/m3 TWA                             | Titanium dioxide / |
|       |   | Coloring agent     |
|       | 100mg/m3 ceiling (particulate)(aerosol) | Ethylene glycol    |
|       | 1000ppm TWA                             | Ethyl alcohol      |
| EC    | 6mg/m3                                  | Titanium dioxide   |
|       | 52mg/m3(20ppm) TWA(skin),               | Ethylene glycol    |
|       | 104mg/m3(40ppm) STEL(skin)              |                    |
|       | 1000ppm                                 | Ethyl alcohol      |

Personal protective equipment : Not required.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

[ ]: Information of components.

Physical state and form : Liquid.
Color : Green.
Odor : Faint odor.
pH : about 8.2

Boiling point : Not available. [Water/ 100 C]

Melting point :<-10 C

Flash point : Not applicable. [Ethyl alcohol/ 12.2 C(CC)]
Auto ignition temperature : Not applicable. [Ethyl alcohol/ 363 C]

Explosion limits : Not applicable.

[Lower flammable limit / 3.28%, Upper flammable limit / 19.0% < Ethyl alcohol>]

Density : about 1.1 / 25 C

Vapor density (air=1) : Not available. [Ethyl alcohol/ 1.59]

Solubility in water : Soluble. Evaporation rate : Not available. Volatile : 73-76%

### 10. STABILITY AND REACTIVITY

Stability : Stability. Hazardous reactions : Will not occur.

Conditions to avoid : Avoid heat, flames, sparks and other sources of ignition.

Avoid contact with incompatible materials.

Materials to avoid : Not available. Hazardous decomposition products : Not available.

## 11.TOXICOLOGICAL INFORMATION

#### (Information of components)

Acute toxicity

| Ingestion LD50  | >24000mg/kg-Rat      | Titanium dioxide |
|-----------------|----------------------|------------------|
|                 | $\geq$ 5000mg/kg-Rat | Coloring agent   |
|                 | 1650mg/kg-Cat、       | Ethylene glycol  |
|                 | 4700mg/kg-Rat        |                  |
|                 | 3450mg/kg-Mouse      | Ethyl alcohol    |
| Inhalation LC50 | 6820mg/m3-4H-Rat     | Titanium dioxide |
|                 | 20000ppm-10H-Rat     | Ethyl alcohol    |
| Skin LD50       | 9530uL/kg-Rabbit     | Ethylene glycol  |

Local effects Irritant; inhalation, skin, eye Ethylene glycol / Ethyl alcohol

Chronic toxicity and long term toxicity

The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus).

The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration.

Ethylene glycol

Ethyl alcohol

Signs and Symptoms of overexposure and aggravated by exposure

| Inhalation       | irritation,cough                             | Titanium dioxide / Ethylene glycol<br>Ethyl alcohol |
|------------------|--|---|
|                  | headache,nausea                              | Resin   |
|                  | irritation                                   | Coloring agent                                      |
| Skin contact     | irritation                                   | Resin / Coloring agent                              |
|                  | irritation,dry                               | Ethylene glycol / Ethyl alcohol                     |
| Eye contact      | irritation,redness                           | Titanium dioxide / Ethylene glycol                  |
| v                | ·  | Ethyl alcohol                                       |
|                  | irritation                                   | Resin / Coloring agent                              |
| Ingestion        | physiologically inert,intestinal obstruction | Titanium dioxide                                    |
|                  | digestive discomfort                         | Resin   |
|                  | nausea,vomiting                              | Coloring agent / Ethylene glycol                    |
|                  | rash,vomiting                                | Ethyl alcohol                                       |
| Specific effects | IARC Group 2B                                | Titanium dioxide                                    |

## 12. ECOLOGICAL INFORMATION

Not available.

### 13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging: Not applicable.

Revision Date: March 7, 2014

## 14. TRANSPORT INFORMATION

HS Code : 960820

# 15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS) : Titanium dioxide / Ethylene glycol / Ethyl alcohol

EU labeling : Not restricted.

CANADA Hazardous Products Act - Ingredient Disclosure List

1%over Ethylene glycol 0.1%over Ethyl alcohol

Hazard and safety information

Products are manufactured in accordance with ISO 8124-3 " Safety of Toys - Part 3"

## 16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it. The information contained in this sheet are based knowledge of the products at the data: (March 7, 2014). They are given quite sincerely. Moreover the attention of the users is drawn on the risks possibly taken, when a product is used for other utilization than these which it is intended.

# Safety data sheet for chemical products

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K Yellow [POSCA]

**JAPAN** 

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

AUSTRALIA

Australian importer : Mitsubishi Pencil Australia

BAN : 31 085 515 671

Address : 674 Lorimar Street, Port Melbourne VIC 3207

Telephone Number : 03 9646 5630

Emergency Telephone Number: 03 9646 5630

(Monday to Friday 9:00am - 5.00pm, general information only)

Creation Date : August 24, 2001 Revision Date : March 7, 2014

File No. : 010279A Aus Rev. 3.6.07.05

## 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

No hazardous product as specified in Directive 67/548/EEC or 1999/45/EC

Label elements :-

Other hazards : Not available.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a mixture : Mixture

Chemical nature: Component parts : Ink

| Chemical or generic name | CAS No.    | TSCA       | EINECS No. | Concentration range (wt%) |
|--------------------------|------------|------------|------------|---------------------------|
| Water                    | 7732-18-5  | Registered | 2317912    | 50- 80                    |
| Titanium dioxide         | 13463-67-7 | Registered | 2366755    | < 10                      |
| Coloring agents          | Registered | Registered | Registered | < 10                      |
| Resins                   | Registered | Registered | Registered | < 10                      |
| Ethylene glycol          | 107-21-1   | Registered | 2034733    | < 10                      |
| Ethyl alcohol            | 64-17-5    | Registered | 2005786    | < 10                      |

Other parts : Other parts are excluded from 'chemical substances'.

### 4. FIRST-AID MEASURES

#### Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

2/5 Creation Date: August 24, 2001 Revision Date: March 7, 2014

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention. Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 3.8g]

### 5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.

Use extinguishing agents appropriate for surrounding fire. Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions: Do not wash away into shower or water way. Methods for cleaning up: Wipe off by dry cloth and wash with water.

: In accordance with national, state and local regulations.

## 7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards. Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.

: Recap after use.

Keep out of the reach of infants.Avoid contact with skin and eyes.

Precautions : Not available. Safe handling advice : Not available.

Storage:

Technical measures : Keep away from oxidizing materials, ignition sources and

high temperature.

Storage condition : Avoid direct sunlight.

: Do not leave the products in high temperature space.

Recommended temperature: 0-30 C.

Incompatible products : Not available.
Packaging materials : Not applicable.

Revision Date: March

## 8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

| OSHA  | 15mg/m3 TWA (Total dust)                | Titanium dioxide   |
|-------|---|--------------------|
|       | 5mg/m3(Respirable fraction),            | Coloring agent     |
|       | 15mg/m3(Total dust) [Nuisance Dust]     |                    |
|       | 1000ppm TWA                             | Ethyl alcohol      |
| ACGIH | 10mg/m3 TWA                             | Titanium dioxide / |
|       |   | Coloring agent     |
|       | 100mg/m3 ceiling (particulate)(aerosol) | Ethylene glycol    |
|       | 1000ppm TWA                             | Ethyl alcohol      |
| EC    | 6mg/m3                                  | Titanium dioxide   |
|       | 52mg/m3(20ppm) TWA(skin),               | Ethylene glycol    |
|       | 104mg/m3(40ppm) STEL(skin)              |                    |
|       | 1000ppm                                 | Ethyl alcohol      |

Personal protective equipment : Not required.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

[ ]: Information of components.

Physical state and form : Liquid. Color : Yellow. Odor : Faint odor. Нα : about 8.3

Boiling point : Not available. [Water/ 100 C]

Melting point :<-10 C

Flash point : Not applicable. [Ethyl alcohol/ 12.2 C(CC)] Auto ignition temperature : Not applicable. [Ethyl alcohol/ 363 C]

**Explosion limits** : Not applicable.

[Lower flammable limit / 3.28%, Upper flammable limit / 19.0% < Ethyl alcohol>]

Density : about 1.1 / 25 C

Vapor density (air=1) : Not available. [Ethyl alcohol/ 1.59]

Solubility in water : Soluble. Evaporation rate : Not available. Volatile : 74-77%

## 10. STABILITY AND REACTIVITY

Stability : Stability. Hazardous reactions : Will not occur.

Conditions to avoid : Avoid heat, flames, sparks and other sources of ignition.

Avoid contact with incompatible materials.

Materials to avoid : Not available. Hazardous decomposition products : Not available.

## 11.TOXICOLOGICAL INFORMATION

(Information of components)

Acute toxicity

| Ingestion LD50  | >24000mg/kg-Rat      | Titanium dioxide |
|-----------------|----------------------|------------------|
|                 | $\geq$ 5000mg/kg-Rat | Coloring agent   |
|                 | 1650mg/kg-Cat、       | Ethylene glycol  |
|                 | 4700mg/kg-Rat        |                  |
|                 | 3450mg/kg-Mouse      | Ethyl alcohol    |
| Inhalation LC50 | 6820mg/m3-4H-Rat     | Titanium dioxide |
|                 | 20000ppm-10H-Rat     | Ethyl alcohol    |
| Skin LD50       | 9530uL/kg-Rabbit     | Ethylene glycol  |

Local effects Irritant; inhalation, skin, eye Ethylene glycol / Ethyl alcohol

Chronic toxicity and long term toxicity

The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus).

The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration.

Ethylene glycol

Ethyl alcohol

Signs and Symptoms of overexposure and aggravated by exposure

| Inhalation       | irritation,cough                 | Titanium dioxide / Ethylene glycol<br>Ethyl alcohol |
|------------------|----------------------------------|---|
|                  | irritation                       | Coloring agent                                      |
|                  | headache,nausea                  | Resin   |
| Skin contact     | redness,swelling                 | Coloring agent                                      |
|                  | irritation                       | Resin   |
|                  | irritation,dry                   | Ethylene glycol / Ethyl alcohol                     |
| Eye contact      | irritation,redness               | Titanium dioxide / Ethylene glycol                  |
| ·                |                                  | Ethyl alcohol                                       |
|                  | irritation                       | Resin   |
| Ingestion        | physiologically inert,intestinal | Titanium dioxide                                    |
| C                | obstruction                      |   |
|                  | nausea,vomiting                  | Coloring agent / Ethylene glycol                    |
|                  | digestive discomfort             | Resin   |
|                  | rash,vomiting                    | Ethyl alcohol                                       |
| Specific effects | IARC Group 2B                    | Titanium dioxide                                    |

## 12. ECOLOGICAL INFORMATION

Not available.

## 13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging: Not applicable.

## 14. TRANSPORT INFORMATION

HS Code : 960820

# 15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS)

: Titanium dioxide / Ethylene glycol / Ethyl alcohol

EU labeling : Not restricted.

CANADA Hazardous Products Act - Ingredient Disclosure List

1%overEthylene glycol0.1%overEthyl alcohol

Hazard and safety information

Products are manufactured in accordance with ISO 8124-3 " Safety of Toys - Part 3"

## 16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it. The information contained in this sheet are based knowledge of the products at the data: (March 7, 2014). They are given quite sincerely. Moreover the attention of the users is drawn on the risks possibly taken, when a product is used for other utilization than these which it is intended.

# Safety data sheet for chemical products

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K Pink [POSCA]

**JAPAN** 

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

AUSTRALIA

Australian importer : Mitsubishi Pencil Australia

BAN : 31 085 515 671

Address : 674 Lorimar Street, Port Melbourne VIC 3207

Telephone Number : 03 9646 5630

Emergency Telephone Number: 03 9646 5630

(Monday to Friday 9:00am - 5.00pm, general information only)

Creation Date : August 24, 2001 Revision Date : March 7, 2014

File No. : 010280A Aus Rev. 3.6.07.06

### 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

No hazardous product as specified in Directive 67/548/EEC or 1999/45/EC

Label elements :-

Other hazards : Not available.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a mixture : Mixture

Chemical nature: Component parts : Ink

| Chemical or generic name          | CAS No.    | TSCA       | EINECS No. | Concentration range (wt%) |
|-----------------------------------|------------|------------|------------|---------------------------|
| Water                             | 7732-18-5  | Registered | 2317912    | 50- 80                    |
| Titanium dioxide                  | 13463-67-7 | Registered | 2366755    | 10- 30                    |
| Resins                            | Registered | Registered | Registered | 10- 30                    |
| Ethylene glycol                   | 107-21-1   | Registered | 2034733    | < 10                      |
| Ethyl alcohol                     | 64-17-5    | Registered | 2005786    | < 10                      |
| Coloring agents                   | Registered | Registered | Registered | < 10                      |
| Polyoxyethylene nonylphenyl ether | 9016-45-9  | Registered | Registered | < 1                       |

Other parts : Other parts are excluded from 'chemical substances'.

### 4. FIRST-AID MEASURES

### Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

2/5 Creation Date: August 24, 2001 Revision Date: March 7, 2014

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

#### Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 3.9g]

#### 5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.

Use extinguishing agents appropriate for surrounding fire. Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions: Do not wash away into shower or water way. Methods for cleaning up: Wipe off by dry cloth and wash with water.

: In accordance with national, state and local regulations.

### 7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards. Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.

: Recap after use.

Keep out of the reach of infants.Avoid contact with skin and eyes.

Precautions : Not available. Safe handling advice : Not available.

Storage:

Technical measures : Keep away from oxidizing materials, ignition sources and

high temperature.

Storage condition : Avoid direct sunlight.

: Do not leave the products in high temperature space.

: Recommended temperature: 0-30 C.

Incompatible products : Not available.
Packaging materials : Not applicable.

## 8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

| OSHA  | 15mg/m3 TWA                             | Titanium dioxide / |
|-------|---|--------------------|
|       |   | Coloring agent     |
|       | 1000ppm TWA                             | Ethyl alcohol      |
| ACGIH | 10mg/m3 TWA                             | Titanium dioxide / |
|       |   | Coloring agent     |
|       | 1000ppm TWA                             | Ethyl alcohol      |
|       | 100mg/m3 ceiling (particulate)(aerosol) | Ethylene glycol    |
| EC    | 6mg/m3                                  | Titanium dioxide   |
|       | 52mg/m3(20ppm) TWA(skin),               | Ethylene glycol    |
|       | 104mg/m3(40ppm) STEL(skin)              |                    |
|       | 1000ppm                                 | Ethyl alcohol      |

Personal protective equipment : Not required.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

]: Information of components.

Physical state and form : Liquid. Color : Pink. Odor : Faint odor. рΗ : about 8.0

Boiling point : Not available. [Water/ 100 C]

Melting point :<-10 C

Flash point : Not applicable. [Ethyl alcohol/ 12.2 C(CC)] Auto ignition temperature : Not applicable. [Ethyl alcohol/ 363 C]

**Explosion limits** : Not applicable.

[Lower flammable limit / 3.28%, Upper flammable limit / 19.0% < Ethyl alcohol>]

Density : about 1.2 / 25 C

Vapor density (air=1) : Not available. [Ethyl alcohol/ 1.59]

Solubility in water : Soluble. Evaporation rate : Not available. Volatile : 68-71%

### 10. STABILITY AND REACTIVITY

Stability : Stability. Hazardous reactions : Will not occur.

Conditions to avoid : Avoid heat, flames, sparks and other sources of ignition.

Avoid contact with incompatible materials.

Materials to avoid : Not available. Hazardous decomposition products : Not available.

## 11.TOXICOLOGICAL INFORMATION

### (Information of components)

Acute toxicity

| Ticate toxicity |                                |                                   |
|-----------------|--------------------------------|-----------------------------------|
| Ingestion LD50  | >24000mg/kg-Rat                | Titanium dioxide                  |
|                 | 1000mg/kg-Mouse                | Resin                             |
|                 | 1650mg/kg-Cat、                 | Ethylene glycol                   |
|                 | 4700mg/kg-Rat                  |                                   |
|                 | 3450mg/kg-Mouse                | Ethyl alcohol                     |
|                 | 2950mg/kg-Mouse                | Coloring agent                    |
|                 | 1310mg/kg-Rat                  | Polyoxyethylene nonylphenyl ether |
| Inhalation LC50 | 6820mg/m3-4H-Rat               | Titanium dioxide                  |
|                 | 20000ppm-10H-Rat               | Ethyl alcohol                     |
| Skin LD50       | 9530uL/kg-Rabbit               | Ethylene glycol                   |
|                 | 2ml/kg-Rabbit                  | Polyoxyethylene nonylphenyl ether |
| Local effects   | Irritant;inhalation, skin, eye | Ethylene glycol / Ethyl alcohol   |
|                 | Irritant;eye                   | Polyoxyethylene nonylphenyl ether |

#### Chronic toxicity and long term toxicity

The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus).

Ethylene glycol

The liquid defats the skin. The substance may have effects on the upper

Ethyl alcohol

respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration. .

Signs and Symptoms of overexposure and aggravated by exposure

| Inhalation       | irritation,cough                 | Titanium dioxide / Resin /         |
|------------------|----------------------------------|------------------------------------|
|                  |                                  | Ethylene glycol / Ethyl alcohol    |
|                  | irritation                       | Coloring agent                     |
|                  |                                  | Polyoxyethylene nonylphenyl ether  |
| Skin contact     | mechanical abrasion,irritation   | Resin                              |
|                  | irritation,dry                   | Ethylene glycol / Ethyl alcohol    |
|                  | redness,swelling of skin         | Coloring agent                     |
|                  | irritation                       | Polyoxyethylene nonylphenyl ether  |
| Eye contact      | irritation,redness               | Titanium dioxide / Ethylene glycol |
|                  |                                  | Ethyl alcohol                      |
|                  | irritation                       | Resin                              |
|                  | irritation,eye damage            | Polyoxyethylene nonylphenyl ether  |
| Ingestion        | physiologically inert,intestinal | Titanium dioxide                   |
|                  | digestive discomfort             | Resin                              |
|                  | nausea,vomiting                  | Ethylene glycol / Coloring agent   |
|                  | rash,vomiting                    | Ethyl alcohol                      |
|                  | digestive disorders,diarrhea     | Polyoxyethylene nonylphenyl ether  |
| Specific effects | IARC Group 2B                    | Titanium dioxide                   |
|                  | IARC Group 3                     | Resin                              |

## 12. ECOLOGICAL INFORMATION

Not available.

Revision Date: March 7, 2014

## 13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging: Not applicable.

## 14. TRANSPORT INFORMATION

HS Code : 960820

## 15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS) : Titanium dioxide / Ethylene glycol / Ethyl alcohol

EU labeling : Not restricted.

CANADA Hazardous Products Act - Ingredient Disclosure List

1%over Ethylene glycol 0.1%over Ethyl alcohol

Hazard and safety information

Products are manufactured in accordance with ISO 8124-3 " Safety of Toys - Part 3"

## 16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it. The information contained in this sheet are based knowledge of the products at the data: (March 7, 2014). They are given quite sincerely. Moreover the attention of the users is drawn on the risks possibly taken, when a product is used for other utilization than these which it is intended.

# Safety data sheet for chemical products

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K Light blue [POSCA]

**JAPAN** 

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

**AUSTRALIA** 

Australian importer : Mitsubishi Pencil Australia

BAN : 31 085 515 671

Address : 674 Lorimar Street, Port Melbourne VIC 3207

Telephone Number : 03 9646 5630

Emergency Telephone Number: 03 9646 5630

(Monday to Friday 9:00am - 5.00pm, general information only)

Creation Date : August 24, 2001 Revision Date : March 7, 2014

File No. : 010281A\_Aus Rev. 3.6.07.05

## 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

No hazardous product as specified in Directive 67/548/EEC or 1999/45/EC

Label elements :-

Other hazards : Not available.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a mixture : Mixture

Chemical nature: Component parts : Ink

| Chemical or generic name | CAS No.    | TSCA       | EINECS No. | Concentration range (wt%) |
|--------------------------|------------|------------|------------|---------------------------|
| Water                    | 7732-18-5  | Registered | 2317912    | 50- 80                    |
| Titanium dioxide         | 13463-67-7 | Registered | 2366755    | 10- 30                    |
| Resins                   | Registered | Registered | Registered | < 10                      |
| Ethyl alcohol            | 64-17-5    | Registered | 2005786    | < 10                      |
| Ethylene glycol          | 107-21-1   | Registered | 2034733    | < 10                      |
| 2-Propanol               | 67-63-0    | Registered | 2006617    | < 10                      |
| Coloring agent           | Registered | Registered | Registered | < 10                      |

Other parts : Other parts are excluded from 'chemical substances'.

### 4. FIRST-AID MEASURES

#### Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

2/5 Creation Date: August 24, 2001 Revision Date: March 7, 2014

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 4.2g]

## 5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.

Use extinguishing agents appropriate for surrounding fire. Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions: Do not wash away into shower or water way.

Methods for cleaning up: Wipe off by dry cloth and wash with water.

: In accordance with national, state and local regulations.

#### 7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards. Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.

: Recap after use.

Keep out of the reach of infants.Avoid contact with skin and eyes.

Precautions : Not available. Safe handling advice : Not available.

Storage:

Technical measures : Keep away from oxidizing materials, ignition sources and

high temperature.

Storage condition : Avoid direct sunlight.

: Do not leave the products in high temperature space.

Recommended temperature: 0-30 C.

Incompatible products : Not available. Packaging materials : Not applicable.

Revision Date: March

## 8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

| OSHA  | 15mg/m3 TWA (Total dust)                | Titanium dioxide   |
|-------|---|--------------------|
|       | 1000ppm TWA                             | Ethyl alcohol      |
|       | 400 ppm TWA, 500ppm STEL                | 2-Propanol         |
|       | 5mg/m3(Respirable fraction),            | Coloring agent     |
|       | 15mg/m3(Total dust) [Nuisance Dust]     |                    |
| ACGIH | 10mg/m3 TWA                             | Titanium dioxide / |
|       |   | Coloring agent     |
|       | 1000ppm TWA                             | Ethyl alcohol      |
|       | 100mg/m3 ceiling (particulate)(aerosol) | Ethylene glycol    |
|       | 200ppm TWA, 400ppm STEL                 | 2-Propanol         |
| EC    | 6mg/m3                                  | Titanium dioxide   |
|       | 1000ppm                                 | Ethyl alcohol      |
|       | 52mg/m3(20ppm) TWA(skin),               | Ethylene glycol    |
|       | 104mg/m3(40ppm) STEL(skin)              |                    |

Personal protective equipment : Not required.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

ſ ]: Information of components.

Physical state and form : Liquid. Color : Light blue. Odor : Faint odor. Hg : about 8.4

Boiling point : Not available. [Water/ 100 C]

Melting point : <-10 C

Flash point : Not applicable. [2-Propanol/ 11.7 C] Auto ignition temperature : Not applicable. [Ethyl alcohol/ 363 C]

Explosion limits : Not applicable.

[Lower flammable limit / 2.0%, Upper flammable limit / 12.7% <2-Propanol>]

Density : about 1.2 / 25 C

Vapor density (air=1) : Not available. [2-Propanol/ 2.07-2.10]

Solubility in water : Soluble. Evaporation rate : Not available. Volatile : 69-72%

## 10. STABILITY AND REACTIVITY

Stability Stability. Hazardous reactions : Will not occur.

Conditions to avoid : Avoid heat, flames, sparks and other sources of ignition.

Avoid contact with incompatible materials.

Materials to avoid : Not available. Hazardous decomposition products : Not available.

## 11.TOXICOLOGICAL INFORMATION

(Information of components)

| A ,    |          |
|--------|----------|
| Acute  | toxicity |
| ricate | UOMICIUS |

| 110000 00111010 |                                |                                 |
|-----------------|--------------------------------|---------------------------------|
| Ingestion LD50  | >24000mg/kg-Rat                | Titanium dioxide                |
|                 | 3450mg/kg-Mouse                | Ethyl alcohol                   |
|                 | 1650mg/kg-Cat、                 | Ethylene glycol                 |
|                 | 4700mg/kg-Rat                  |                                 |
|                 | 3600mg/kg-Mouse                | 2-Propanol                      |
|                 | >5000mg/kg-Rat                 | Coloring agent                  |
| Inhalation LC50 | 6820mg/m3-4H-Rat               | Titanium dioxide                |
|                 | 20000ppm-10H-Rat               | Ethyl alcohol                   |
|                 | 11100ppm-4H-Mouse              | 2-Propanol                      |
| Skin LD50       | 9530uL/kg-Rabbit               | Ethylene glycol                 |
|                 | 12800mg/kg-Rabbit              | 2-Propanol                      |
| Local effects   | Irritant;inhalation, skin, eye | Ethyl alcohol / Ethylene glycol |

#### Chronic toxicity and long term toxicity

The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration.

Ethyl alcohol

2-Propanol

The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus). Ethylene glycol

The liquid defats the skin.

2-Propanol

Signs and Symptoms of overexposure and aggravated by exposure

Irritant; inhalation, eye

| 0 1             | 1 88                             | <i>v</i> 1                       |
|-----------------|----------------------------------|----------------------------------|
| Inhalation      | irritation,cough                 | Titanium dioxide / Ethyl alcohol |
|                 |                                  | Ethylene glycol                  |
|                 | headache,nausea                  | Resin                            |
|                 | irritation,nausea                | 2-Propanol                       |
|                 | irritation                       | Coloring agent                   |
| Skin contact    | irritation                       | Resin                            |
|                 | irritation,dry                   | Ethyl alcohol / Ethylene glycol  |
|                 | irritation, absorption           | 2-Propanol                       |
| Eye contact     | irritation,redness               | Titanium dioxide / Ethyl alcohol |
| •               |                                  | Ethylene glycol                  |
|                 | irritation                       | Resin / Coloring agent           |
|                 | irritation,pain                  | 2-Propanol                       |
| Ingestion       | physiologically inert,intestinal | Titanium dioxide                 |
|                 | obstruction                      |                                  |
|                 | digestive discomfort             | Resin                            |
|                 | rash,vomiting                    | Ethyl alcohol                    |
|                 | nausea,vomiting                  | Ethylene glycol                  |
|                 | nausea,stomach pain              | 2-Propanol                       |
|                 | gastric disturbances             | Coloring agent                   |
| pecific effects | IARC Group 2B                    | Titanium dioxide                 |
|                 | IARC Group 3                     | 2-Propanol                       |
|                 |                                  |                                  |

## 12. ECOLOGICAL INFORMATION

Not available.

## 13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging: Not applicable.

### 14. TRANSPORT INFORMATION

HS Code : 960820

### 15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS)

: Titanium dioxide / Ethyl alcohol / Ethylene glycol / 2-Propanol

EU labeling : Not restricted.

CANADA Hazardous Products Act - Ingredient Disclosure List

0.1%over Ethyl alcohol

1%over Ethylene glycol / 2-Propanol

Hazard and safety information

Products are manufactured in accordance with ISO 8124-3 "Safety of Toys - Part 3"

## 16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it. The information contained in this sheet are based knowledge of the products at the data: (March 7, 2014). They are given quite sincerely. Moreover the attention of the users is drawn on the risks possibly taken, when a product is used for other utilization than these which it is intended.

# Safety data sheet for chemical products

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K White [POSCA]

**JAPAN** 

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

**AUSTRALIA** 

Australian importer : Mitsubishi Pencil Australia

BAN : 31 085 515 671

Address : 674 Lorimar Street, Port Melbourne VIC 3207

Telephone Number : 03 9646 5630

Emergency Telephone Number: 03 9646 5630

(Monday to Friday 9:00am - 5.00pm, general information only)

Creation Date : August 24, 2001 Revision Date : March 7, 2014

File No. : 010282A Aus Rev. 3.6.07.05

## 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

No hazardous product as specified in Directive 67/548/EEC or 1999/45/EC

Label elements :-

Other hazards : Not available.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a mixture : Mixture

Chemical nature: Component parts: Ink

| Chemical or generic name | CAS No.    | TSCA       | EINECS No. | Concentration range (wt%) |
|--------------------------|------------|------------|------------|---------------------------|
| Water                    | 7732-18-5  | Registered | 2317912    | 50- 80                    |
| Titanium dioxide         | 13463-67-7 | Registered | 2366755    | 10- 30                    |
| Resins                   | Registered | Registered | Registered | < 10                      |
| Ethyl alcohol            | 64-17-5    | Registered | 2005786    | < 10                      |
| Ethylene glycol          | 107-21-1   | Registered | 2034733    | < 10                      |
| 2-Propanol               | 67-63-0    | Registered | 2006617    | < 10                      |

Other parts : Other parts are excluded from 'chemical substances'.

### 4. FIRST-AID MEASURES

## Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

2/5 Creation Date: August 24, 2001 Revision Date: March 7, 2014

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention. Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 4.3g]

### 5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.

Use extinguishing agents appropriate for surrounding fire. Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions: Do not wash away into shower or water way. Methods for cleaning up: Wipe off by dry cloth and wash with water.

: In accordance with national, state and local regulations.

#### 7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards. Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.

: Recap after use.

Keep out of the reach of infants.Avoid contact with skin and eyes.

Precautions : Not available. Safe handling advice : Not available.

Storage:

Technical measures : Keep away from oxidizing materials, ignition sources and

high temperature.

Storage condition : Avoid direct sunlight.

: Do not leave the products in high temperature space.

Recommended temperature: 0-30 C.

Incompatible products : Not available.

Packaging materials : Not applicable.

## 8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

| OSHA          | 15mg/m3 TWA (Total dust)                | Titanium dioxide |
|---------------|---|------------------|
|               | 1000ppm TWA                             | Ethyl alcohol    |
|               | 400 ppm TWA, 500ppm STEL                | 2-Propanol       |
| ACGIH         | 10mg/m3 TWA                             | Titanium dioxide |
|               | 1000ppm TWA                             | Ethyl alcohol    |
|               | 100mg/m3 ceiling (particulate)(aerosol) | Ethylene glycol  |
|               | 200ppm TWA, 400ppm STEL                 | 2-Propanol       |
| $\mathbf{EC}$ | 6mg/m3                                  | Titanium dioxide |
|               | 1000ppm                                 | Ethyl alcohol    |
|               | 52mg/m3(20ppm) TWA(skin),               | Ethylene glycol  |
|               | 104mg/m3(40ppm) STEL(skin)              |                  |

Personal protective equipment : Not required.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

ſ ]: Information of components.

Physical state and form : Liquid. Color : White. Odor : Faint odor. pН : about 8.1

Boiling point : Not available. [Water/ 100 C]

Melting point : <-10 C

Flash point : Not applicable. [2-Propanol/ 11.7 C] Auto ignition temperature : Not applicable. [Ethyl alcohol/ 363 C]

Explosion limits : Not applicable.

[Lower flammable limit / 2.0%, Upper flammable limit / 12.7% <2-Propanol>]

Density : about 1.3 / 25 C

Vapor density (air=1) : Not available. [2-Propanol/ 2.07-2.10]

Solubility in water : Soluble. Evaporation rate : Not available. Volatile : 65-68%

### 10. STABILITY AND REACTIVITY

Stability : Stability. Hazardous reactions : Will not occur.

Conditions to avoid : Avoid heat, flames, sparks and other sources of ignition.

Avoid contact with incompatible materials.

Materials to avoid : Not available. Hazardous decomposition products : Not available.

## 11.TOXICOLOGICAL INFORMATION

(Information of components)

| A .   |      | • ,  |
|-------|------|------|
| Acute | LOX1 | CILV |
|       |      |      |

| Ingestion LD50  | >24000mg/kg-Rat<br>3450mg/kg-Mouse<br>1650mg/kg-Cat,<br>4700mg/kg-Rat | Titanium dioxide<br>Ethyl alcohol<br>Ethylene glycol |
|-----------------|---|--|
|                 | 3600mg/kg-Mouse   | 2-Propanol   |
| Inhalation LC50 | 6820mg/m3-4H-Rat  | Titanium dioxide                                     |
|                 | 20000ppm-10H-Rat  | Ethyl alcohol  |
|                 | 11100ppm-4H-Mouse   | 2-Propanol   |
| Skin LD50       | 9530uL/kg-Rabbit  | Ethylene glycol                                      |
|                 | 12800mg/kg-Rabbit   | 2-Propanol   |
| Local effects   | Irritant;inhalation, skin, eye  | Ethyl alcohol / Ethylene glycol                      |

Irritant; inhalation, eye Chronic toxicity and long term toxicity

The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration.

Ethyl alcohol

2-Propanol

The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus).

The liquid defats the skin.

Ethylene glycol

2-Propanol

Signs and Symptoms of overexposure and aggravated by exposure

| Inhalation       | irritation,cough                 | Titanium dioxide / Ethyl alcohol |
|------------------|----------------------------------|----------------------------------|
|                  |                                  | Ethylene glycol                  |
|                  | headache,nausea                  | Resin                            |
|                  | irritation,nausea                | 2-Propanol                       |
| Skin contact     | irritation                       | Resin                            |
|                  | irritation,dry                   | Ethyl alcohol / Ethylene glycol  |
|                  | irritation, absorption           | 2-Propanol                       |
| Eye contact      | irritation,redness               | Titanium dioxide / Ethyl alcohol |
| ·                |                                  | Ethylene glycol                  |
|                  | irritation                       | Resin                            |
|                  | irritation,pain                  | 2-Propanol                       |
| Ingestion        | physiologically inert,intestinal | Titanium dioxide                 |
|                  | obstruction                      |                                  |
|                  | digestive discomfort             | Resin                            |
|                  | rash,vomiting                    | Ethyl alcohol                    |
|                  | nausea, vomiting                 | Ethylene glycol                  |
|                  | nausea,stomach pain              | 2-Propanol                       |
| Specific effects | IARC Group 2B                    | Titanium dioxide                 |
|                  | IARC Group 3                     | 2-Propanol                       |

## 12. ECOLOGICAL INFORMATION

Not available.

Revision Date: March

## 13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging: Not applicable.

## 14. TRANSPORT INFORMATION

HS Code : 960820

## 15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS)

: Titanium dioxide / Ethyl alcohol / Ethylene glycol / 2-Propanol

EU labeling : Not restricted.

CANADA Hazardous Products Act - Ingredient Disclosure List

0.1%over Ethyl alcohol

1%over Ethylene glycol / 2-Propanol

Hazard and safety information

Products are manufactured in accordance with ISO 8124-3 " Safety of Toys - Part 3"

## 16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it. The information contained in this sheet are based knowledge of the products at the data: (March 7, 2014). They are given quite sincerely. Moreover the attention of the users is drawn on the risks possibly taken, when a product is used for other utilization than these which it is intended.