

Safety Data Sheet
according to WHS Regulations

Printing date 07.05.2020

Version number 3.0

Revision: 07.05.2020

1 Identification

- **Product identifier**
- **Trade name:** KREUL Magic Marble Marbling paint 20 ml
- **Article number:** 73201 - 73237, 73600, 73610 - 73614, 73703, 732091
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Paint
For artists and hobby user.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
C. KREUL GmbH & Co. KG
Carl-Kreul-Straße 2
D-91352 HALLERNDORF
DEUTSCHLAND
Tel. + 49 (0)9545 / 925 - 0
Fax + 49 (0)9545 / 925 - 511
E-Mail: info@c-kreul.de
- Importer
Zart Art Pty Ltd
48 Overseas Drive
Noble Park North 3174
VIC
Australia
Ph: 61 3 9890 1867 Fax: 61 3 9898 6527
- **Further information obtainable from:** Ph: 61 3 9890 1867 Fax: 61 3 9898 6527
- **Emergency telephone number:** Poison Centre 13 11 26

2 Hazard(s) Identification

- **Classification of the substance or mixture**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning
- **Hazard statements**
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety Data Sheet

according to WHS Regulations

Printing date 07.05.2020

Version number 3.0

Revision: 07.05.2020

(Contd. of page 1)

Other hazards

Vapours may form explosive mixtures with air. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/ electrical equipment). Take precautionary measures against static discharges.

Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition and Information on Ingredients

Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3	1-methoxy-2-propanol ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	25- $<$ 50%
CAS: 64742-48-9 EC number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, $<$ 2% aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336	10- $<$ 20%
EC number: 918-481-9	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclenes, $<$ 2% aromatics ⚠ Asp. Tox. 1, H304; Flam. Liq. 4, H227	5- $<$ 10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	5- $<$ 10%

Additional information:

Benzene (EINECS 200-753-7) $<$ 0.1%. (Note P Annex VI to Directive (EC) No 1272/2008)
For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

Description of first aid measures

· **General information:** Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

Seek immediate medical advice.

After skin contact:

Wash with water and acidic soap.

If skin irritation continues, consult a doctor.

After eye contact:

Remove contact lenses.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Administer medicinal carbon.

A person vomiting while laying on their back should be turned onto their side.

Seek immediate medical advice.

Information for doctor:

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

5 Fire Fighting Measures

Extinguishing media

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Advice for firefighters

· **Protective equipment:** Wear self-contained respiratory protective device.

· **Additional information** Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

Safety Data Sheet

according to WHS Regulations

Printing date 07.05.2020

Version number 3.0

Revision: 07.05.2020

(Contd. of page 2)

Mount respiratory protective device.

- **Environmental precautions:**

Keep contaminated washing water and dispose of appropriately.
In case of seepage into the ground inform responsible authorities.
Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and Storage

- **Handling:**

- **Precautions for safe handling**

Take note of emission threshold.
Prevent formation of aerosols.
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.

- **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.
Fumes can combine with air to form an explosive mixture.
Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** Store in a cool location.

- **Information about storage in one common storage facility:**

Do not store together with oxidising and acidic materials.
Do not store together with alkalis (caustic solutions).

- **Further information about storage conditions:**

Keep container tightly sealed.
Store receptacle in a well ventilated area.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

107-98-2 1-methoxy-2-propanol	
WES	Short-term value: 553 mg/m ³ , 150 ppm Long-term value: 369 mg/m ³ , 100 ppm
108-65-6 2-methoxy-1-methylethyl acetate	
WES	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
108-65-6 2-methoxy-1-methylethyl acetate	
WES	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk

- **DNELs**

64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics		
Oral	long-term exposure-systemic effects	300 mg/kg (general population)
Dermal	long-term exposure-systemic effects	300 mg/kg bw/d (general population) 300 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	900 mg/m ³ (general population) 1,500 mg/m ³ (worker)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	long-term exposure-systemic effects	1.67 mg/kg (general population)
Dermal	long-term exposure-systemic effects	54.8 mg/kg bw/d (general population) 153.5 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	33 mg/m ³ (general population) 275 mg/m ³ (worker)
107-98-2 1-methoxy-2-propanol		
Oral	long-term exposure-systemic effects	33 mg/kg (general population)

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations

Printing date 07.05.2020

Version number 3.0

Revision: 07.05.2020

(Contd. of page 3)

Dermal	long-term exposure-systemic effects	183 mg/kg bw/d (general population) 78 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	43.9 mg/m ³ (general population) 369 mg/m ³ (worker)

· **PNECs**

107-98-2 1-methoxy-2-propanol

water	100 mg/l
freshwater	10 mg/l
marine water	1 mg/l
sewage treatment plant (STP)	100 mg/l
freshwater sediment	52.3 mg/kg
marine sediment	5.2 mg/kg

108-65-6 2-methoxy-1-methylethyl acetate

water	635 mg/l
freshwater	0.635 mg/l
marine water	0.0635 mg/l
sewage treatment plant (STP)	100 mg/l
freshwater sediment	3.29 mg/kg
marine sediment	0.329 mg/kg
soil	0.29 mg/kg

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not eat, drink, smoke or sniff while working.

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

· **Respiratory protection:**

Not necessary if room is well-ventilated.

Use suitable respiratory protective device when high concentrations are present.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.38 mm

Value for the permeation: Level ≤ 4 h

· **As protection from splashes gloves made of the following materials are suitable:**

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.3 mm

Value for the permeation: Level $\leq 10 - 30$ min

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Colour: According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

(Contd. on page 5)

Safety Data Sheet

according to WHS Regulations

Printing date 07.05.2020

Version number 3.0

Revision: 07.05.2020

(Contd. of page 4)

· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.
· Flash point:	25 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	>200 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	13.8 Vol %
· Vapour pressure:	Not determined.
· Density at 20 °C:	0.9–1.1 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 40 °C:	>20.5 mm ² /s
· Solvent content:	
Organic solvents:	65-80 %
VOC (EC)	67.42–77.69 %
· Other information	No further relevant information available.

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Keep away from oxidizing agents, strong alkaline and acidic materials.
- **Hazardous decomposition products:**
In case of fire, the following can be released:
Carbon monoxide and carbon dioxide

11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:**

107-98-2 1-methoxy-2-propanol

Oral	LD50	5,660 mg/kg (rat)
Dermal	LD50	13,000 mg/kg (rabbit)

64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rab)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rab)
Inhalative	LC50/4h	35.7 mg/m ³ (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.

AU

(Contd. on page 6)

Safety Data Sheet

according to WHS Regulations

Printing date 07.05.2020

Version number 3.0

Revision: 07.05.2020

(Contd. of page 5)

12 Ecological Information

· **Toxicity**

· **Aquatic toxicity:**

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

LC50/48h >1,000 mg/l (oncorhynchus mykiss)

EC50/48h >1,000 mg/l (daphnia magna)

EC50/72h >1,000 mg/l (pseudokirchneriella subcapitata)

108-65-6 2-methoxy-1-methylethyl acetate

LC50/96h 134 mg/l (oncorhynchus mykiss)

EC50/48h >500 mg/l (daphnia magna)

· **Persistence and degradability** No further relevant information available.

· **Behaviour in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Danger to drinking water if even extremely small quantities leak into the ground.

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **ADG, IMDG, IATA**

UN1263

· **UN proper shipping name**

· **ADG**

1263 PAINT

· **IMDG, IATA**

PAINT

· **Transport hazard class(es)**

· **ADG, IMDG, IATA**



· **Class**

3 Flammable liquids.

· **Label**

3

· **Packing group**

· **ADG, IMDG, IATA**

III

· **Environmental hazards:**

Not applicable.

· **Special precautions for user**

Warning: Flammable liquids.

· **Hazard identification number (Kemler code):**

30

· **EMS Number:**

F-E, S-E

· **Stowage Category**

A

· **Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **Transport category**

3

· **Tunnel restriction code**

D/E

(Contd. on page 7)

Safety Data Sheet

according to WHS Regulations

Printing date 07.05.2020

Version number 3.0

Revision: 07.05.2020

(Contd. of page 6)

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Australian Inventory of Chemical Substances**

All ingredients are listed.

- **Standard for the Uniform Scheduling of Medicines and Poisons**

None of the ingredients is listed.

- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard statements**

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

- **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category P5c** FLAMMABLE LIQUIDS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H226 Flammable liquid and vapour.

H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

- **Department issuing SDS:** Product Safety Department

- **Contact:** Ph: 61 3 9890 1867 Fax: 61 3 9898 6527

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 4: Flammable liquids – Category 4

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

AU