



MATERIAL SAFETY DATA SHEET

Revision Date: 16/04/2019

Transport/Fire Emergency: **000** (Emergency Services)
Medical Emergency: **131126** (Poisons information)

409 GORE ST FITZROY VIC 3065
T: +61 3 9419 5559 F: +61 3 9419 4232
E: info@hfaw.com

Speedball Speed Clean (4534)

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION	
PRODUCT NAME:	Speedball Screen Filler
OTHER NAMES:	
APPLICATION OF SUBSTANCE:	Silkscreen cleaning agent.
MANUFACTURED BY:	Speedball Art Products Co. 2301 Speedball Road Statesville , NC 28677 USA
CONTACT NUMBERS:	Phone: 704-978-4166 Fax: 1-704-838-1472 Email: budmartin@speedballart.com

2. HAZARDOUS INFORMATION	
Effects and symptoms of acute exposure: exposure may cause acute or delayed damage to the lungs. Skin irritant. Eye irritant. Medical conditions usually aggravated by over exposure to this product: asthma, kidney disease, pregnancy.	
MANUFACTURER'S CODE:	4534
UN NUMBER:	N/A
DANGEROUS GOODS CLASS AND SUBSIDIARY RISK:	N/A
HAZCHEM CODE:	N/A
POISONS SCHEDULE NUMBER:	N/A
PACKAGING GROUP:	N/A
HAZARD CATEGORY:	N/A
CLASS:	N/A

3. COMPOSITION / INFORMATION ON INGREDIENTS	
Sodium Metasilicate: 1.22960% CAS/EC#: 6834-92-0 PEL/TLV (MG/M#): N/A	

4. FIRST AID MEASURES	
GENERAL:	Medical conditions usually aggravated by over exposure to this product: asthma, kidney disease, pregnancy.
INHALATION:	N/A
EYE CONTACT:	If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care. Contact may result in severe eye pain and impairment of vision.
SKIN CONTACT:	Flush with water. Contact may result in blistering or ulcers of the skin.
INGESTION:	Dilute by giving water. See doctor.

5. FIRE FIGHTING MEASURES	
EXTINGUISHING MEDIA:	N/A
DO NOT USE:	N/A
DEGREE OF FIRE RISK:	Non combustible, non explosive
RECOMMENDATIONS:	N/A

6. ACCIDENTAL RELEASE MEASURES	
Floor may be slippery; use care to avoid falling. Absorb spillage with non-combustible, absorbent material.	

7. HANDLING AND STORAGE	
HANDLING:	Good industrial hygiene practice requires that exposure be maintained below the TLV. This is preferably achieved through the provision of adequate ventilation. When exposure cannot be adequately controlled in this way, personal respiratory protection should be employed.
STORAGE:	Keep out of reach of children.

8. EXPOSURE CONTROL AND PERSONAL PROTECTION	
ENGINEERING MEASURES:	Adequate ventilation.
<i>PERSONAL PROTECTION</i>	
RESPIRATORY PROTECTION:	Use NIOSH-certified mask for dusts and a locally exhausting hood appropriate for the operation.
HAND PROTECTION:	When using wear impermeable protective gloves.
EYE PROTECTION:	Safety goggles or glasses
SKIN PROTECTION:	N/A

9. PHYSICAL AND CHEMICAL PROPERTIES	
APPEARANCE:	Clear liquid
FLASH POINT:	N/A
BOILING POINT:	N/A
VAPOUR PRESSURE:	N/A
VAPOUR DENSITY:	N/A
SPECIFIC GRAVITY:	N/A
REACTIVITY IN WATER:	Non reactive
MELTING POINT:	N/A

10. STABILITY AND REACTIVITY
Stable.

11. TOXICOLOGICAL INFORMATION
Effects and symptoms of acute exposure: exposure may cause acute or delayed damage to the lungs. Skin irritant. Eye irritant. Medical conditions usually aggravated by over exposure to this product: asthma, kidney disease, pregnancy.

12. ECOLOGICAL INFORMATION
No harmful effects known other than those associated with suspended inert solids in water.

13. DISPOSAL CONSIDERATIONS
Observe all Federal, State and local laws concerning health and environment.

14. TRANSPORT INFORMATION
N/A

15. REGULATORY INFORMATION
Contents of this SDS comply with OSHA Hazard Communication Standard 29 CFR 1901.1200 EPA SARA title 3 chemical listings: none Section 302.4 Extremely Hazardous Substances (40 CFR 355): none Section 313 Toxic Chemicals (40 CFR 372): none

16. OTHER INFORMATION
N/A